

CISCO UNIFIED IP PHONE 7912G

Cisco Unified IP phones---an integral component of the Cisco Unified IP Communications system---provide superior levels of integrated business features and converged communications---levels far beyond today's conventional voice systems. As the market leader in true IP telephony, Cisco continues to deliver unsurpassed end-to-end data and voice-over-IP (VoIP) solutions, offering the most complete, stylish, and fully featured IP phone portfolio in the industry.

The Cisco Unified IP Phone 7912G provides core business features and addresses the communication needs of a cubicle worker who conducts low to medium telephone traffic. The Cisco Unified IP Phone 7912G offers four dynamic soft keys that guide a user through call features and functions. The graphic capability of the display provides a rich user experience by providing calling information and intuitive access to features. In addition, XML applications deliver impressive applications and network data to the Cisco Unified IP Phone 7912G display.

The Cisco Unified IP Phone 7912G supports an integrated Ethernet switch, providing LAN connectivity to a colocated PC. In addition, the Cisco Unified IP Phone 7912G supports inline power, which allows the phone to receive power over the LAN. This capability gives the network administrator centralized power control, translating into greater network availability. The combination of inline power and Ethernet switch support reduces cabling needs to a single wire to the desktop.

Figure 1. Cisco Unified IP Phone 7912G



CISCO UNIFIED IP PHONE 7912G FEATURES

The Cisco Unified IP Phone 7912G is designed to be easy to use with conveniently placed features.

- Pixel-based display---A pixel-based display provides intuitive access to calling features.
- Four soft keys dynamically present calling options to the user. The scroll toggle bar allows easy movement through the displayed information.
- “Menu” key---This key allows users to quickly access information such as call logs and phone settings.
 - The user can retrieve voice-mail messages.
 - The user can display missed calls, outgoing calls that have been placed, and incoming calls that have been received.
 - The user can set various preferences such as ring types and display contrast.
- “Hold” key---This lighted key provides users a red visual indication that they have placed a call on hold.

- A volume-control toggle provides easy decibel-level adjustments of the handset and ringer.
- The handset is hearing-aid compatible (meets American Disabilities Act [ADA] requirements).
- A single-position foot stand provides optimum display viewing and comfortable use of buttons and keys. The foot stand can be removed to allow wall mounting via mounting holes located on the base of the phone.
- XML Applications can be delivered to the display.

CALLING FEATURES

The Cisco Unified IP Phone 7912G is designed to grow with system capabilities. Features will keep pace with new changes via software updates to the phone Flash memory. Examples of currently available features include:

- Support of a single line or directory number
- Calling name and number display
- Call waiting
- Call forward
- Call transfer
- Support of Extension Mobility
- Three-way calling (conference)
- On-hook dialing, predialing, and off-hook dialing
- Redial
- Call hold
- Call monitor (speaker only, no microphone)
- “Messages” soft key that allows access to voicemail messages
- Four speed dials configurable at the Cisco Unified CallManager

NETWORK FEATURES

- Cisco Discovery Protocol
- Automatic IEEE 802.1Q (voice virtual LAN [VVLAN]) configuration
- IEEE 802.1Q /p VLAN tagging and traffic prioritization
- 802.1Q VLAN-based switching of traffic between the phone and access switch
- Differentiated Services Code Point (DSCP) tagging
- G.711a, G.711u, and G.729ab audiocompression coders-decoders (codecs)
- Integrated Ethernet switch
- 10/100BASE-T Ethernet connection through an RJ-45 interface for LAN connectivity
- Software upgrade supported using a Trivial File Transfer Protocol (TFTP) server
- Provisioning of network parameters through Dynamic Host Configuration Protocol (DHCP)
- Voice activity detection, silence suppression, comfort-noise generation, and error concealment

PROTOCOLS SUPPORTED

- Compatible with Cisco Unified CallManager Version 3.3(2) and later, using the Skinny Client Control Protocol (SCCP) protocol
- SIP (RFC 2543)

PHYSICAL SPECIFICATIONS

- Dimensions (H x W x D): 6.5 x 7 x 6 in. (20.3 x 17.67 x 15.2 cm)
- Weight: 1.9 lb (0.9 kg)

POWER SUPPLY

- Inline power
- Power can also be supplied locally using an optional AC to 48-VDC power adapter (CP-PWR-CUBE-3=), which requires one of the following country-specific cords.

AC Country Power Cords

- CP-PWR-CORD-AP= (Asia Pacific)
- CP-PWR-CORD-AR= (Argentina)
- CP-PWR-CORD-AU= (Australia)
- CP-PWR-CORD-CE= (Central Europe)
- CP-PWR-CORD-JP= (Japan)
- CP-PWR-CORD-NA= (North America)
- CP-PWR-CORD-SW= (Switzerland)
- CP-PWR-CORD-UK= (United Kingdom)

TEMPERATURE

- Operating temperature: 32 to 104°F (0 to 40°C)
- Relative humidity: 10 to 95% (noncondensing)
- Storage temperature: 14 to 140°F (-10 to 60°C)

CERTIFICATION

Regulatory Compliance

- CE Marking

Safety

- UL 60950
- CSA-C22.2 No. 60950
- EN 60950
- IEC 60950
- AS/NZS 3260
- TS 001

EMC

- FCC Part 15 (CFR 47) Class B
- ICES-003 Class B
- EN55022 Class B
- CISPR22 Class B
- AS/NZS 3548 Class B
- VCCI Class B
- EN55024
- EN50082-1
- EN 61000-3-2
- EN 61000-3-3
- EN 61000-6-1

Telecom

- FCC Part 68 (CFR 47) (HAC)

SERVICE AND SUPPORT

Cisco Unified IP Communications services and support reduce the cost, time, and complexity associated with implementing a converged network. Cisco and its partners have designed and deployed some of today's largest and most complex IP communications networks---meaning that they understand how to integrate an IP communications solution into your network. Cisco design tools and best practices ensure that the solution best fits your business needs from the start, eliminating costly redesigns and downtime. Cisco proven methods ensure a sound implementation that will deliver the functions and features you expect---on time. Support services include remote network operations, network management tools to administer the converged application and network infrastructure, and technical support services.

Through these services, your organization benefits from the experience gained by Cisco and its partners. Taking advantage of this valuable experience, you can create and maintain a resilient, converged network that will meet your business needs today---and in the future.

ORDERING INFORMATION

Table 1 lists part numbers for the Cisco Unified IP Phone 7912G and Cisco Unified CallManager.

Table 1. Part Numbers

Part Number	Description
CP-7912G-A	Cisco Unified IP Phone 7912 with hardware update
SW-CCM-UL-7912	Station user license for Cisco Unified CallManager
SW-SMH-UL-7912	Station user license for SIP

Cisco offers a standard one-year warranty. A Cisco SMARTnet[®] optional service agreement is available.

Accessories Ordering Information

An optional locking wall mount kit is available:

- CP-LCKNGWALLMNT2=

FOR MORE INFORMATION

For more information about Cisco products, call or visit:

- United States and Canada: (toll free) 800 553-NETS (6387)
- Europe: 32 2 778 4242
- Australia: 612 9935 4107
- Other: 408 526-7209
- <http://www.cisco.com>



Corporate Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International
BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Website at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus
Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland
Israel • Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland
Portugal • Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden
Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2005 Cisco Systems, Inc. All rights reserved. CCIP, CCSP, the Cisco *Powered* Network mark, Cisco Unity, Follow Me Browsing, FormShare, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MeetingPlace, MGX, MICA, the Networkers logo, Networking Academy, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, ScriptShare, SlideCast, SMARTnet, StrataView Plus, Stratm, SwitchProbe, TeleRouter, The Fastest Way to Increase Your Internet Quotient, TransPath, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Website are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0502R)
205215.BL_ETMG_SK_5.05